CLEAVER GOLF Assembly Instructions - Page 1.



WHAT YOU'LL NEED: Scissors, glue (or a glue stick), a ruler, a utility knife, and a piece of corrugated cardboard (at least 8" X 10" in size). A black marker is optional.

FOLDING TIP: It's helpful to 'score' the fold lines before folding. You can use an old ink pen, a knitting needle, the end of a paper clip, or any metal object that will crease the paper without tearing it. (I use a pointy little tool from a manicure kit.) Scoring will help you fold much more quickly and precisely.

ASSEMBLY:

Cut out the CLEAVER LEFT piece on Parts Page 1. Glue the CLEAVER LEFT to the corrugated cardboard, as shown in Figure 1. Use the utility knife to cut away the extra cardboard.

Then cut out the CLEAVER RIGHT piece on Parts Page 1 and glue it to the reverse side of the cardboard, as shown in Figure 2. Trim if needed. You can now use a black marker to darken the cardboard edge if you want to (by laying the marker's tip sideways on the edge of the cardboard, or by laying the piece flat and tracing around it with the marker).

Cut out the CLEAVER LEFT and CLEAVER RIGHT pieces on Parts Page 2. Glue to the cardboard in the same manner as before and again trim as needed.

Next, cut out one of the EYE FRONT pieces on Parts Page 2. Fold the eight dark gray tabs DOWNWARD. Then fold the eight metal panels with rivets DOWNWARD. Thinking of the piece as a wheel, gently curve each of the eight 'spokes' DOWNWARD (curving them over your finger tips works fine).

Glue the eight dark gray tabs to the unprinted side of the adjacent metal panels, forming a dome as shown in Figure 3.

Cut out one of the EYE BACK pieces on Parts Page 2. Fold and assemble the EYE BACK in the same manner as we did the EYE FRONT.

The EYE FRONT is slightly larger than the EYE BACK, so the EYE FRONT should fit over the EYE BACK the way a lid fits over a box. Place glue on the gray EYE BACK panels, and then carefully place the riveted EYE FRONT panels directly over them and glue in place, as shown in Figure 4. Use plenty of glue and press gently until the glue takes hold. (If needed, you can push a toothpick through the gaps so there's something inside to push against.)

(Continued on next page...)

CLEAVER GOLF Assembly Instructions - Page 2.

Cut out the remaining EYE FRONT and EYE BACK on Parts Page 3 and assemble in the same manner as before.

Now cut out the GREEN PLAYER POST on Parts Page 4. Fold the blank gray panel DOWNWARD and then fold DOWNWARD between all six filigree panels. Glue the blank gray panel to the unprinted side of the opposite filigree panel, forming a cone as shown in Figure 5.

Cut out the BLUE PLAYER POST on Parts Page 4 and assemble in the same manner as the GREEN PLAYER POST.

Now all we need are seven loops for the players to hit the balls through. Cut out one of the LOOP pieces on Parts Page 5. Fold the two small end panels UPWARD. Then fold DOWNWARD along the center line and glue the four filigree panels without gems to the unprinted side of the four filigree panels with gems. Now, with the gems facing upward, fold DOWNWARD between all four panels with gems. Bend the LOOP until it resembles Figure 6.

Cut out all six remaining LOOP pieces and assemble in the same manner. Congratulations! Your Cleaver Golf Game is now ready to play.

Pro Tip: If you prefer to stand while playing, you can use the cleavers like golf clubs by tying or taping them to a yardstick, small curtain rod, wooden dowel, or similar item.

CLEAVER GOLF Game Rules:

Players set up the two POSTS and seven LOOPS as shown below. Players flip a coin to see who goes first, then take turns hitting the balls. Each player begins by placing their ball between their POST and the first LOOP. They must then hit their ball through the loops in the order shown below. First player to knock their ball against the opponent's POST wins the game.

