

THE STEEL JAW Assembly Instructions.



WHAT YOU'LL NEED: Scissors, Elmer's glue (or a glue stick), a needle, a toothpick, a pen or pencil, and some string (about two feet should be enough). A ruler or other straight-edge is helpful for scoring and folding.

FOLDING TIP: It's helpful to 'score' the fold line before folding. You can use an old ink pen, a knitting needle, the end of a paper clip, or any metal object that will crease the paper without tearing it. Scoring will help you fold much more quickly and precisely.

ASSEMBLY:

Begin by cutting out the TOP piece and the FRONT piece. On the FRONT piece, fold the two outer blank tabs DOWNWARD and then fold all nine metal tabs DOWNWARD. Glue the two outer blank tabs to the back of the mask as shown in Figure 1. Trim if needed. Then glue the nine metal tabs to the blank areas on the TOP piece as shown in Figure 2. Fold the blank triangles on the two outer metal tabs DOWNWARD and glue them to the inside of the mask as shown in Figure 3. Now we'll add some string to wear the mask. Use the needle to puncture the small black dots on both sides of the mask. Push the toothpick through these two holes to enlarge them a little. Then push the tip of a pen or pencil through the holes to enlarge them enough for the string to pass through. Tie a piece of string (around 12 inches long) to each side of the mask, as shown in Figure 4. Your steel jaw is now finished!